SPEC SHEET

Grand Oak Plank S

PRODUCT

Wide-format oak flooring for design freedom, not manufacturing convenience. Widths and lengths run varied or fixed, exactly as the design intent demands. Matched to the space instead of a factory standard. The floor reads as a deliberate choice, not a standard product laid down.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 1000 mm - max. 5000 mm
WIDTHS	min. 40 mm - max. 500 mm
THICKNESS	19 mm · 5 mm top layer + 9,5 mm core + 4,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

Custom patterns on request

GRADES



Prime

Natural

Refined Heart

Bold

Character

Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
INSTALLATION	full-surface glue-down
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Grand Oak Plank Essential

PRODUCT

A compact oak plank in fixed widths and lengths at an accessible price. The full range of colours and haptics remains available.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Spruce · Spruce



DIMENSIONS

LENGTHS	min. 1800 mm - max. 2400 mm
WIDTHS	min. 180 mm - max. 240 mm
THICKNESS	15 mm · 4 mm top layer + 9 mm core + 2 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths, random lengths

random widths, fixed lengths



fixed widths, random lengths

fixed widths, fixed lengths

Custom patterns on request

GRADES



Prime



Medium



Rustic

Photos are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Medium · Rustic
HAPTICS	Sanded · Brushed · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Medium 1,0 mm
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
INSTALLATION	full-surface glue-down
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Grand Oak Plank L

PRODUCT

Wide-format oak flooring for design freedom, not manufacturing convenience. Widths and lengths run varied or fixed, exactly as the design intent demands. Matched to the space instead of a factory standard. The floor reads as a deliberate choice, not a standard product laid down.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 5000 mm - max. 13500 mm
WIDTHS	min. 40 mm - max. 500 mm
THICKNESS	19 mm · 5 mm top layer + 9,5 mm core + 4,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths



random widths,
fixed lengths · room lenght



fixed widths,
random lengths



fixed widths,
fixed lengths · room lenght

Custom patterns on request

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
INSTALLATION	full-surface glue-down
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Grand Oak Plank Herringbone 15

PRODUCT

Oak flooring planks laid in a 45° interlocked Herringbone pattern. Widths and lengths are fixed, set by the pattern itself.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Spruce · Spruce



DIMENSIONS

LENGTHS	min. 450 mm - max. 1500 mm
WIDTHS	min. 40 mm - max. 200 mm
THICKNESS	15 mm · 4 mm top layer + 9 mm core + 2 mm back layer
	Custom dimensions on request

SPEC SHEET

Grand Oak Plank Herringbone 19

PRODUCT

Oak flooring planks laid in a 45° interlocked Herringbone pattern. Widths and lengths are fixed, set by the pattern itself.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 1500 mm
WIDTHS	min. 40 mm - max. 200 mm
THICKNESS	19 mm · 5 mm top layer + 9,5 mm core + 4,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



Herringbone

GRADES



Prime



Natural



Refined Heart



Bold



Character

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
INSTALLATION	full-surface glue-down
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Grand Oak Plank Chevron 15

PRODUCT

Oak flooring planks laid in Chevron pattern at 45° or 60°. Widths and lengths are fixed, set by the pattern itself.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Spruce · Spruce



DIMENSIONS

LENGTHS	min. 450 mm - max. 1500 mm
WIDTHS	min. 40 mm - max. 200 mm
THICKNESS	15 mm · 4 mm top layer + 9 mm core + 2 mm back layer
	Custom dimensions on request

SPEC SHEET

Grand Oak Plank Chevron 19

PRODUCT

Oak flooring planks laid in Chevron pattern at 45° or 60°. Widths and lengths are fixed, set by the pattern itself.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 1500 mm
WIDTHS	min. 40 mm - max. 200 mm
THICKNESS	19 mm · 5 mm top layer + 9,5 mm core + 4,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



Chevron 45°

Chevron 60°

GRADES



Prime



Natural



Refined Heart



Bold



Character

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
INSTALLATION	full-surface glue-down
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying - upon prior request

SPEC SHEET

Wall & Ceiling Oak Architectural

PRODUCT

Wide-format oak paneling for walls, sized to the design intent, not a catalog standard. Lighter and more stable than solid plank, which makes installation easier and lowers cost. The finished wall matches the exact oak used on the floor beneath it.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 8000 mm
WIDTHS	min. 40 mm - max. 400 mm · shiplap min. 250 mm
THICKNESS	15 mm · 1,5 mm top layer + 12 mm core + 1,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

GRADES



Prime

Natural

Refined Heart

Bold



Character

Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Wall & Ceiling Oak Gap

PRODUCT

A wide, clean rift-sawn nickel-gap plank at premium quality. Supplied in fixed or varying lengths and available at large volumes. Built for projects where scale and consistency matter as much as the look.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 3500 mm
WIDTHS	min. 50 mm - max. 250 mm
THICKNESS	19 mm · 1 mm + 4 mm top layer + 9,5 mm core + 4,5 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

GRADES



Prime Rift

Grade Image is for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime Rift
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	Custom Nickel Gap max. 3 mm deep & wide

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Wall & Ceiling Oak Spline

PRODUCT

The nickel-gap look of a solid plank at a fraction of the cost. Spline runs on a 1mm veneer, our thinnest. The look reads at the top of the range, the material cost stays low.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 8000 mm
WIDTHS	min. 60 mm - max. 220 mm
THICKNESS	15 mm · 1,5 mm top layer + 12 mm core + 1,5 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths



random widths,
fixed lengths · room lenght



fixed widths,
random lengths



fixed widths,
fixed lengths · room lenght

Custom patterns on request

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Wall & Ceiling Oak Basic

PRODUCT

Supplied in fixed or varying lengths, for projects where the wall needs to match the colour of the other oak elements on a limited budget. The same oak tone at an accessible price.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · MDF · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 3000 mm
WIDTHS	min. 75 mm - max. 350 mm
THICKNESS	14 mm · 1 mm top layer + 12 mm core + 1 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

GRADES



Prime



Natural

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm · Square Edge / no Bevel

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Wall & Celing Oak Supersolid 19

PRODUCT

Supersolid gives carpenters full-depth timber to work with. Railings, grilles and other details can be machined directly into the plank. Multiple solid oak layers are glued into one full-thickness core, more stable than a single piece and without its length and width limits.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced multi-layer, Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 8000 mm
WIDTHS	min. 40 mm - max. 400 mm
THICKNESS	19 mm, 23 mm, 27 mm, ... - 1,5 mm top layer + 4 mm multi layers oak + 1,5 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

Custom patterns on request

GRADES



Prime



Natural



Refined Heart

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large 1,5 mm · Square Edge / no Bevel

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	suitable
UNDERFLOOR COOLING	suitable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Wall & Ceiling Oak Pyroguard

PRODUCT

Wall cladding certified for fire resistance, built to the standards required in public spaces. Visually matched to the rest of the project's oak elements, cleared for use where fire safety regulations apply.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · MDF · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 8000 mm
WIDTHS	min. 180 mm - max. 400 mm
THICKNESS	19 mm · 1,5 mm top layer + 16 mm core + 1,5 mm back layer
	Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths

random widths,
fixed lengths · room lenght

fixed widths,
random lengths

fixed widths,
fixed lengths · room lenght

GRADES



Prime

Natural

Refined Heart

Bold



Character

Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm · Square Edge / no Bevel

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Wall & Ceiling Oak Alu

PRODUCT

A custom construction for surfaces with specific stability or weight requirements. Built around an aluminum core which carries structural loads a wood core or solid construction cannot.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Alu · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 6200 mm
WIDTHS	min. 180 mm - max. 400 mm
THICKNESS	1,5 mm top layer + 6, 10, 15, 20, 25 mm core + 1,5 mm back layer

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths



random widths,
fixed lengths · room lenght



fixed widths,
random lengths



fixed widths,
fixed lengths · room lenght

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request

SPEC SHEET

Slat Oak 50

PRODUCT

Engineered construction lets these slats reach lengths, thicknesses, and widths that would warp or waste solid timber. Each slat is built up from bonded layers, a method suited to long, thin dimensions. The dimension is set by the project, not by the material's natural limits.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 5000 mm
WIDTHS	min. 50 mm - max. 400 mm
THICKNESS	min. 25 mm - max. 100 mm · 1,5 mm top layer + pine core + 1,5 mm back layer
	Custom dimensions on request

GRADES



Prime



Natural



Refined Heart

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart
HAPTICS	Sanded · Brushed
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Interior Door Oak 45

PRODUCT

Custom doors, manufactured to measure for each project. Built on a frame system designed for a refined appearance and a straightforward installation.

COLLECTION

The Classic Collection is built for flexibility. Colour, grade and haptic are chosen independently, within the range available for each product, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

HEIGHTS	min. 2000 mm - max. 4000 mm
WIDTHS	min. 600 mm - max. 1200 mm
THICKNESS	45 mm · 3,5 mm oak + 3,5 mm pine cross layer + 31 mm pine core + 3,5 mm pine cross layer + 3,5 mm oak or custom Custom dimensions on request

VENEER LAYOUT



Single Leaf



Two-Leaf



Multi-Leaf

Custom layouts on request

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large Bevel 1,5 mm · Flush / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2701
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %) Optional extra drying – upon prior request

SPEC SHEET

Tread Set Oak 40 Tread and Riser

PRODUCT

A matched tread and riser, supplied as a set. Standard thickness is 40 mm; custom dimensions are built directly from shop drawings when the project calls for it.

COLLECTION

The Classic Collection is built for flexibility. Colour, grade and haptic are chosen independently, within the range available for each product, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 900 mm - max. 7000 mm
WIDTHS	min. 180 mm - max. 500 mm
THICKNESS	40 mm standard · 15 mm - 50 mm customized
	Custom dimensions on request

SPEC SHEET

Tread Set Oak Mitered

PRODUCT

A matched tread and riser, supplied as a set. Standard thickness is 40 mm; custom dimensions are built directly from shop drawings when the project calls for it.

COLLECTION

The Classic Collection is built for flexibility. Colour, grade and haptic are chosen independently, within the range available for each product, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Pine · Oak



DIMENSIONS

LENGTHS	min. 900 mm - max. 7000 mm
WIDTHS	min. 180 mm - max. 500 mm
THICKNESS	19 mm standard · 5 mm top layer + 9,5 mm pine + 4,5 mm back layer
	Custom dimensions on request

GRADES


Prime


Natural


Refined Heart


Bold


Character


Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large Bevel 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Millwork Panel Oak 19

PRODUCT

Finished panels in the same grade and veneer as the project's floors and walls, supplied directly to the contractor or millworker. Cabinetry, built-ins, and custom joinery come out matching the rest of the project exactly.

COLLECTION

The Classic Collection is built for flexibility. Colour, grade and haptic are chosen independently, within the range available for each product, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · MDF · Oak



DIMENSIONS

LENGTHS	min. 3000 mm - max. 4000 mm
WIDTHS	1200 mm
THICKNESS	19 mm · 5 mm top layer + 9 mm core + 5 mm back layer
	Custom dimensions on request

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large Bevel 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Box Beam Oak

PRODUCT

Pre-mitered, custom-sized blanks for wrapping existing beams or building the beam look from scratch. Every dimension is made to size and mitered ready for use. Choose flat-packed for on-site assembly, or pre-assembled and delivered complete.

COLLECTION

The Classic Collection is built for flexibility. Colour, grade and haptic are chosen independently, within the range available for each product, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: Engineered balanced 3-layer, Oak · Plywood · Oak



DIMENSIONS

LENGTHS	min. 450 mm - max. 12000 mm
WIDTHS · HEIGHTS	min. 95 mm - max. 500 mm
THICKNESS	19 mm · 5 mm top layer + 9,5 mm plywood core + 4,5 mm back layer
	Custom dimensions on request

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Sanded · Brushed · Naturally Dried · Hand-Planed · Saw-cut · Custom on request
COLOURS	TDW Classic Collection · Custom
PROTECTION	Natural Oil · Varnish · Soap
BEVELS	V - Micro 0,6 mm / Medium 1,0 mm / Large Bevel 1,5 mm · Square Edge / no Bevel
OPTIONS	Butterfly inserts · repairs of open knots with insert knots

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Sawn Veneer Oak 1,8

PRODUCT

The base layer behind every product that needs length and width, without needing to withstand wear. At 1,8 mm, sawn veneer delivers the full look of oak, at a fraction of the mass and cost of a full wear layer.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: solid



DIMENSIONS

LENGTHS	min. 400 mm - max. 8000 mm
WIDTHS	min. 180 mm - max. 400 mm
THICKNESS	sanded 1,8 mm
	Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths



random widths,
fixed lengths · room lenght



fixed widths,
random lengths



fixed widths,
fixed lengths · room lenght

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur – quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Raw · Sanded
COLOURS	TDW Classic Collection · Custom

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)
	Optional extra drying – upon prior request

SPEC SHEET

Sawn Veneer Oak 5,5

PRODUCT

The base layer behind every product that needs to withstand wear. At 5,5 mm, sawn veneer carries a full wear layer, deep enough to sand and refinish over the life of the floor.

COLLECTION

The Classic Collection is built for flexibility. Any colour can be combined with any grade and any haptic, from light to deep tones that work across every interior and every style.

SECTIONAL VIEW

Construction: solid



DIMENSIONS

LENGTHS	min. 400 mm - max. 8000 mm
WIDTHS	min. 180 mm - max. diameter log
THICKNESS	raw 7 mm · calibrated 5,5 mm · sanded 5 mm

Custom dimensions on request

INSTALLATION PATTERNS



random widths,
random lengths



random widths,
fixed lengths · room lenght



fixed widths,
random lengths



fixed widths,
fixed lengths · room lenght

GRADES



Prime



Natural



Refined Heart



Bold



Character



Core

Grade Images are for guidance only. Wood is a natural material, colour and grain can vary.

SURFACE SPECIFICATIONS

WOOD TYPE	Quercus robur - quercus petrea
GRADES	Prime · Natural · Refined Heart · Bold · Character · Core
HAPTICS	Raw · Sanded
COLOURS	TDW Classic Collection · Custom

TECHNICAL INFORMATION

CE-CERTIFICATION	EN 13489(14342)
PEFC	PEFC/04-31-2700
FORMALDEHYDE EMISSION	E1
FIRE CLASS	Dfl - s1
UNDERFLOOR HEATING	not applicable
UNDERFLOOR COOLING	not applicable
APPLICATION AREA	private · commercial
WOOD MOISTURE	7 % (+/- 2 %)

Optional extra drying – upon prior request